



選購規格 Optional

- 10HP馬達 motor
- 緊急停止 EMG stop
- 雙手壓按鈕 (替換腳踏開關)
Hands push twin press button (exchange with foot switch)
- 雙手壓按鈕 (可與腳踏開關切換使用)
Hands push twin press button (also can switch to use foot switch)
- 雙手壓按鈕 (雙按鈕未同步無法動作)
Hands push twin press button (if it not press at same time, that cannot cutting when hands press the buttons.)
- 電源保護開關
Power protecting swich
- 鋸切高度調整
Cutting height adjustment
- 鋸切保護蓋
Cutting safety cover
- 鋸切保護蓋 (可掀式)
Cutting safety cover (flipper type)
- 防手切保護裝置
Protecting device for prevent hands to cut
- 開啟前門斷風保護裝置
Protecting device for stop air supply when open front door.
- 開啟前門斷電保護裝置
Protecting device for stop power supply when open front door.
- 更換鋸片斷風保護裝置
Protecting device for stop air supply when it replace saw blade.
- 更換鋸片斷電開門裝置
Protecting device for stop power supply when it replace saw blade.

快速精準
得利得益



FURNIMATE WOOD WORKING MACHINERY CO., LTD.

地址：台灣省台中市豐原區三豐路967巷62號
NO.62 LANE967, SAN FENG ROAD, FENG YUAN DIST, TAICHUNG, TAIWAN
P.O.BOX: 375 FENG YUAN, TAIWAN.
Tel: +886-4-25248780. +886-4-25225778 Fax: +886-4-25238923
E-mail: furnimat@ms43.hinet.net



The Best
Cutting Machine

CUT-OFF SAW CS-18 SERIES
www.furnimate.ecatalog.tw



CS18-L

木工用裁切機械規格表

Specification of cut-off saw for wood material

鋸切尺寸(厚x寬)	Cutting size (TxW)	2"x12"、3"x11"、4"x10
鋸片尺寸	Saw blade size	18"x120Tx3.4x25.4
鋸片轉速(60Hz&50Hz)	RPM	3630RPM/3050RPM
鋸切速度	Cutting ability	81 times/min
空氣壓力	Air pressure inquiry	4-5 Kg/cm ²
集塵罩出口徑	Diameter of Dusty collector	4"
馬達	Motor	7.5HP (10HP optional)
控制模式	Control mode	腳踏開關 foot switch
工作台面尺寸	Working table size	660x700mm
工作台面高度	Working table height	890mm
淨重	N.W.	350Kgs
毛重	G.W.	410Kgs
裝箱尺寸(長x寬x高)	Packing size (LxWxH)	940x850x1350mm

※備註:本公司隨時進行研究改善的工作,尺寸規格若有變更,恕不另行通知。
Dimensions and specifications shown in the catalogue are subject to change without prior notice.



CS18-S

高安全性裁切機械規格表

High security cut-off machine specification

機械規格表同CS-18L機型。
Same with the specification of CS-18L

安全裝置 Safety devices

緊急停止 EMG stop

雙手壓按鈕(可與腳踏開關切換使用)
Hands push twin press button (also can switch to use foot switch)

雙手壓按鈕(雙按鈕未同步無法動作)
Hands push twin press button (if it not press at same time, that cannot cutting when hands press the buttons.)

電源保護開關 Power protecting switch

鋸切保護蓋(可掀式) Cutting safety cover (flipper type)

開啟前門斷風保護裝置
Protecting device for stop air supply when open front door.

開啟前門斷電保護裝置
Protecting device for stop power supply when open front door.

更換鋸片斷風保護裝置
Protecting device for stop air supply when it replace saw blade.

更換鋸片斷電開門裝置
Protecting device for stop power supply when it replace saw blade.

Feature



CS18-M

鋁用裁切機械規格表

Specification of cut-off saw for aluminum material

鋸切尺寸(厚x寬)	Cutting size (TxW)	2"x12"、3"x11"、4"x10
鋸片尺寸	Saw blade size	18"x120Tx3.4x25.4
鋸片轉速(60Hz&50Hz)	RPM	3600RPM/3200RPM
驅動方式	Drive mode	Pneumatic空壓 & Hydraulic油壓
鋸切速度	Cutting ability	25 times/min
空氣壓力	Air pressure inquiry	4-5 Kg/cm ²
集塵罩出口徑	Diameter of Dusty collector	4"
馬達	Motor	7.5HP (10HP optional)
控制模式	Control mode	腳踏開關 foot switch
工作台面尺寸	Working table size	660x700mm
工作台面高度	Working table height	890mm
淨重	N.W.	350Kgs
毛重	G.W.	410Kgs
裝箱尺寸(長x寬x高)	Packing size (LxWxH)	940x850x1350mm
鋸切高度調整	Cutting Safety cover	
自動噴油裝置	Auto. lubricator	